


























Supplier:	KEEPOWER TECHNOLOGY CO., LIMITED
Address:	Bld4, Fengmenao Industrial Park, Longgang District, Shenzhen 518129, China
Phone:	+86 755 8995 6056
Fax:	+86 755 8930 9659
E-Mail:	<a href="mailto:info@keepower.com.cn">info@keepower.com.cn</a>
Website:	<a href="http://www.keepower.com.cn">www.keepower.com.cn</a>

**Keepower Protected Battery Series**

Size	Model	Type	Nominal Voltage/Capacity	Photo	Cell	Specifications
18650	KP-18650-3400 Protected Battery	Li-ion	3.7V 3400mAh		Japan Brand	1) Min. Capacity: 3250mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1700mA 4) Standard Charge Time: 4 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 6800mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-18650-3200A Protected Battery	Li-ion	3.7V 3200mAh		Japan Brand	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 909mA 4) Standard Charge Time: 5 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Max. Continuous Discharge Current: 3636mA 7) Protection Trip Current: 10A 8) Dimension: (D)18.50*(H)69.00mm 9) Cycle Life: Over 500 charge & discharge cycles 10) Weight: Max. 49.0g
	KP-18650-3200B Protected Battery	Li-ion	3.7V 3200mAh		Korea Brand	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.35V±0.05 3) Standard Charge Current: 1600mA 4) Standard Charge Time: 4 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 640mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-18650-3100 Protected Battery	Li-ion	3.7V 3100mAh		Japan Brand	1) Min. Capacity: 3000mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1550mA 4) Standard Charge Time: 4 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 610mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-18650-3000 Protected Battery	Li-ion	3.7V 3000mAh		Korea Brand	1) Min. Capacity: 2900mAh 2) Charge Voltage: 4.35V±0.05 3) Standard Charge Current: 1500mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 600mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-18650-2900 Protected Battery	Li-ion	3.7V 2900mAh		Japan Brand	1) Min. Capacity: 2750mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1450mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 580mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 7) Cycle Life: Over 500 charge & discharge cycles 8) Weight: Max. 49.0g
	KP-18650-2800 Protected Battery	Li-ion	3.7V 2800mAh		Korea Brand	1) Min. Capacity: 2700mAh 2) Charge Voltage: 4.35V±0.05 3) Standard Charge Current: 1400mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 560mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 7) Cycle Life: Over 500 charge & discharge cycles 8) Weight: Max. 49.0g
18650	KP-18650-2600A Protected Battery	Li-ion	3.7V 2600mAh		Japan Brand	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1750mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 3.0V 6) Standard Discharge Current: 520mA 7) Standard Discharge Cut-off Current: 30mA 8) Protection Trip Current: 10A 9) Dimension: (D)18.50*(H)69.00mm 7) Cycle Life: Over 500 charge & discharge cycles 8) Weight: Max. 48.0g

Size	Model	Type	Nominal Voltage/Capacity	Photo	Cell	Specifications
18650	KP-18650-2600B Protected Battery	Li-ion	3.7V 2600mAh		Korea Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 2500mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 1300mA</li> <li>4) Standard Charge Time: 3 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 520mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 10A</li> <li>6) Dimension: (D)18.50*(H)69.00mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 48.0g</li> </ol>
	KP-18650-2200 Protected Battery	Li-ion	3.7V 2200mAh		Korea Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 2150mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 1100mA</li> <li>4) Standard Charge Time: 3 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 440mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 10A</li> <li>6) Dimension: (D)18.50*(H)69.00mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 46.0g</li> </ol>
14430	KP-14430 Protected Battery	Li-ion	3.7V 700mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 600mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 3A</li> <li>6) Dimension: (D)14.35*(H)46.10mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 18.0g</li> </ol>
14500	KP-14500A Protected Battery	Li-ion	3.7V 800mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 700mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 3A</li> <li>6) Dimension: (D)14.25*(H)52.50mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 22.0g</li> </ol>
	KP-14500B Protected Battery	Li-ion	3.7V 840mAh		Japan Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 750mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 3A</li> <li>6) Dimension: (D)14.25*(H)52.50mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 22.0g</li> </ol>
14650	KP-14650 Protected Battery	Li-ion	3.7V 1000mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 1000mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 500mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 500mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 3A</li> <li>6) Dimension: (D)14.25*(H)67.50mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 28.0g</li> </ol>
16340	KP-16340 Protected Battery	Li-ion	3.7V 700mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 650mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 300mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 150mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 3A</li> <li>6) Dimension: (D)16.70*(H)35.60mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 20.0g</li> </ol>
16650	KP-16650 Protected Battery	Li-ion	3.7V 2100mAh		Japan Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 2000mAh</li> <li>2) Charge Voltage: 4.35V±0.05</li> <li>3) Standard Charge Current: 480mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 1000mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 5A</li> <li>6) Dimension: (D)16.70*(H)68.50mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 40.0g</li> </ol>
17500	KP-17500 Protected Battery	Li-ion	3.7V 1200mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 1100mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 5A</li> <li>6) Dimension: (D)17.50*(H)53.0mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 40.0g</li> </ol>

Size	Model	Type	Nominal Voltage/Capacity	Photo	Cell	Specifications
17670	KP-17670 Protected Battery	Li-ion	3.7V 1500mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 1400mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 5A</li> <li>6) Dimension: (D)17.50*(H)70.0mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 40.0g</li> </ol>
18350	KP-18350 Protected Battery	Li-ion	3.7V 900mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 800mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 450mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 7A</li> <li>6) Dimension: (D)18.45*(H)38.20mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 25.0g</li> </ol>
18500	KP-18500A Protected Battery	Li-ion	3.7V 1500mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 1450mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 7A</li> <li>6) Dimension: (D)18.50*(H)52.50mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 35.0g</li> </ol>
	KP-18500B Protected Battery	Li-ion	3.7V 1700mAh		Japan Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 1600mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 400mA</li> <li>4) Standard Charge Time: 2 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 400mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 7A</li> <li>6) Dimension: (D)18.50*(H)53.00mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 40.0g</li> </ol>
26650	KP-26650-4500 Protected Battery	Li-ion	3.7V 4500mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 4500mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 1500mA</li> <li>4) Standard Charge Time: 4 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 2000mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 15A</li> <li>6) Dimension: (D)26.50*(H)69.00mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 95.0g</li> </ol>
	KP-26650-5200 Protected Battery	Li-ion	3.7V 5200mAh		China Brand	<ol style="list-style-type: none"> <li>1) Min. Capacity: 5100mAh</li> <li>2) Charge Voltage: 4.20V±0.05</li> <li>3) Standard Charge Current: 1500mA</li> <li>4) Standard Charge Time: 4 hours</li> <li>5) Standard Discharge Cut-off Voltage: 2.75V</li> <li>6) Standard Discharge Current: 2000mA</li> <li>7) Standard Discharge Cut-off Current: 30mA</li> <li>8) Protection Trip Current: 15A</li> <li>6) Dimension: (D)26.50*(H)69.00mm</li> <li>7) Cycle Life: Over 500 charge &amp; discharge cycles</li> <li>8) Weight: Max. 95.1g</li> </ol>

\* Please contact [info@keppower.com.cn](mailto:info@keppower.com.cn) for more information.